

Ⓜ
CONCENTRO

Defining the
future of sound.

ELAC Concentro M

One look tells you this is no ordinary loudspeaker. The sophisticated cabinet features curves that allow optimum propagation and dispersion of sound waves.



Sophisticated aluminum woofers Through the use of aluminum, resonances that affect the linearity of common paper cones can be placed beyond the driver's operating frequency range.



VX-Technology
The acclaimed drive unit, which combines the renowned JET tweeter with a ring-radiator midrange driver in a concentric arrangement, provides the foundation of these speakers' remarkable sound.



VX-JET 5 Tweeter
Delivering true high-definition sound, ELAC's JET 5 tweeter enralls with its lightning-fast response and wide dynamic range.

Is it just a bit smaller?

Yes, but that's not all! The Concentro M exhibits characteristic design cues, but creates its own unique visual impact.

Concentro proves that the whole can be even greater than the sum of its many state-of-the-art parts.

A variable VX chassis lets you to tailor the sound to your listening area, while four 220 mm woofers, installed in a pulse-compensated configuration, ensure exceptional bass delivery in any room.

ELAC

Concentro M

CONCENTRO M

Height	1450 mm with spikes
Width	460 mm with base
Depth	535 mm with base
Weight	90 kg
Type	3-Way, bass reflex
Woofer	4 x 220 mm Ø AS, cone
Midrange	1 x 70 / 140 mm Ø, AS-XR ring radiator
Tweeter	JET 5 Core, modified
Crossover frequency	180 2700 Hz
Nominal power handling	300 W
Minimal impedance	2,8 Ω at 380 Hz
Peak power handling	400 W
Frequency range (IEC 268-5)	24 - 50000 Hz
Sensitivity	88 dB/2,83 V/m
Suitable for amplifiers from ... to	4 - 8 Ω
Nominal impedance	4 Ω
Recommended amplifier power	80 - 600 W/channel
Finishes	Black High Gloss, White High Gloss
Accessories included in delivery	bi-wiring set, gloves, tool set



CONCENTRO

